



NORTH 69 ELITE HYBRID

Full Synthetic Motor Oil

Features & Benefits

- ★ Outstanding protection for cold starts
- ★ Superior defense against engine wear
- ★ Resists breakdown from heat and oxidation
- ★ Maintains stability under high temperatures
- ★ Helps prevent sludge and deposit buildup

Product Description

NORTH 69 Full Synthetic is engineered with ultra-refined synthetic base oils and advanced additive technology. It delivers instant protection from the moment you start your engine, even in extreme cold (-40°C).

It not only meets but exceeds API SP standards and outperforms the stringent requirements set by both domestic and international automakers for high performance engines.

Properties

- Minimizes oil evaporation and burn-off at high temperatures
- Special detergent formula prevents sludge and deposit buildup, ensuring a clean engine
- Enhances engine longevity and reliability under extreme conditions
- Excellent resistance to aging for extended oil life

Meets or Exceeds Requirements

Meets or Exceeds	SAE 0W-16
API SP/GF-6B, SN	✓
Toyota	✓
Honda	✓

Typical Results

SAE Grade	Test Method	SAE 0W-16
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.842
Viscosity @ 40°C cSt	ASTM D445	7.2
Viscosity @ 100°C cSt	ASTM D2270	172
Viscosity Index	ASTM D5950	-48°C (-54°F)
Pour Point, °C	ASTM D1500	2.5
Color	ASTM D5293	4200 (-35)
Cold Cranking Simulator at (°C), cP	ASTM D6616	5.2
High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	2.4
Noack Volatility, % loss	ASTM D6375	12
Calcium, wt. %	ASTM D5185	0.135
Zinc, wt. %	ASTM D5185	0.085
Phosphorus, wt. %	ASTM D5185	0.076
Sulfur, wt. %	ASTM D4951	0.3
Boron, wt	ASTM D5185	0.023
Sulfated Ash, wt. %	ASTM D874	0.9
Nitrogen, wt. %	ASTM D4629	0.104
Pumping Viscosity at (°C), cP	ASTM D4684	15,500 (-40)
Shear Stability	ASTM D 6278	6.6

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 22-37-82.



NORTH 69 ELITE HYBRID

Full Synthetic Motor Oil

Health & Safety

When used as directed and in accordance with the Material Safety Data Sheet (MSDS), this product is not expected to pose health risks.

To request an MSDS, Please contact your direct sales Distributor or via email info@north69oils.com or call 1-888-660-2913

This product is intended for its specified use only.
When disposing of used oil, follow proper environmental protection guidelines.

Products Numbers

Product Name	Package Size	Part Numbers
SAE 0W-16 HYBRID Full Synthetic	Bottle 1L	N69ET-E10059
	Box (1L X 12)	N69ET-E10059X12
	Jug 5L	N69ET-E10019
	Box (5L x 4)	N69ET-E10019X4
	Jug 18.9L	N69ET-E10089