



# NORTH 69 ELITE EURO

## Full Synthetic Motor Oil

### Features & Benefits

- ★ Outstanding protection for cold starts
- ★ Superior defense against engine wear
- ★ Resists breakdown from heat and oxidation
- ★ Maintains stability under high temperatures
- ★ Helps prevent sludge and deposit buildup

### Product Description

**NORTH 69 Full Synthetic** is engineered with ultra-refined synthetic base oils and advanced additive technology. It delivers instant protection from the moment you start your engine, even in extreme cold (-40°C). It not only meets but exceeds API SP standards and outperforms the stringent requirements set by both domestic and international automakers for high performance engines.

### Properties

- Minimizes oil evaporation and burn-off at high temperatures
- Special detergent formula prevents sludge and deposit buildup, ensuring a clean engine
- Enhances engine longevity and reliability under extreme conditions
- Excellent resistance to aging for extended oil life

### Specifications & Approvals

Meets or Exceeds	SAE 0W-30 LOW SAPS
ACEA C2, C3	✓
VW 504.00, 507.00	✓
BMW LongLife-04	✓
Porsche C30	✓
MB 229.52	✓
Fiat 955535.GS1	✓
Fiat 955535.DS1	✓

### Typical Results

SAE Grade	Test Method	SAE 0W-30 LOW SAPS
<b>Specific Gravity</b> @ 60°F (15.6°C)	ASTM D4052	0.842
<b>Cold crank (CCS) cP</b> @ -35°C	ASTM D5293	5750
<b>Viscosity</b> @ 40°C cSt	ASTM D445	64.0
<b>Viscosity</b> @ 100°C cSt	ASTM D445	12.0
<b>Viscosity Index</b>	ASTM D2270	178
<b>Pour Point, °C</b>	ASTM D97	-51
<b>Flash Point, °C</b>	ASTM D92	232
<b>TBN, mgKOH/g</b>	ASTM D2896	8.0
<b>Sulfated Ash, wt. %</b>	ASTM D874	0.7

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 22-37-82.



# NORTH 69 ELITE EURO

Full Synthetic Motor Oil

## Health & Safety

When used as directed and in accordance with the Material Safety Data Sheet (MSDS), this product is not expected to pose health risks.

To request an MSDS, Please contact your direct sales Distributor or via email [info@north69oils.com](mailto:info@north69oils.com) or call 1-888-660-2913

This product is intended for its specified use only. When disposing of used oil, follow proper environmental protection guidelines.

## Products Numbers

Product Name	Package Size	Part Numbers
SAE 0W-30 EURO LOW SAPS Full Synthetic	Bottle 1L	N69ET-S7159
	Box (1L X 12)	N69ET-S7159X12
	Jug 5L	N69ET-S7119
	Box (5L x 4)	N69ET-S7119X4
	Jug 18.9L	N69ET-S7179