



# NORTH 69 ELITE EURO

## Full Synthetic Motor Oil

### Features & Benefits

- ★ Outstanding protection for cold starts
- ★ Superior defense against engine wear
- ★ Resists breakdown from heat and oxidation
- ★ Maintains stability under high temperatures
- ★ Helps prevent sludge and deposit buildup

### Specifications & Approvals

Meets or Exceeds	SAE 0W-30 SP
ACEA: C2, A5/B5, A1/B1	✓
BMW: LL-01 FE, LL-12 FE	✓
API: SP/SN+/SM/SL	✓
AC Delco: 88864605	✓
GM: dexos1™ GEN2, GEN3	✓
VW/Audi: 502.00/503.00/503.01/506.00/506.01	✓
Chrysler: MS-13340/MS-6395/68291576AA	✓
Fiat: 9.55535-DS1/9.5535-GS1	✓
Ford: M2C950-A/WSS M2C953-A1	✓
Jaguar Land Rover: JST.JLR 03-5006 JST.JLR 03-5007	✓
Mercedes Benz: 229.3/229.5/229.52/229.6	✓
Porsche: C30	✓
RN: 0700/0710	✓

### Product Description

**NORTH 69 Full Synthetic** is engineered with ultra-refined synthetic base oils and advanced additive technology. It delivers instant protection from the moment you start your engine, even in extreme cold (-40°C).

It not only meets but exceeds API SP standards and outperforms the stringent requirements set by both domestic and international automakers for high performance engines.

### Properties

- Minimizes oil evaporation and burn-off at high temperatures
- Special detergent formula prevents sludge and deposit buildup, ensuring a clean engine
- Enhances engine longevity and reliability under extreme conditions
- Excellent resistance to aging for extended oil life

### Typical Results

SAE Grade	Test Method	SAE 0W-30 SP
<b>Cold crank (CCS) cP @ -35°C</b>	ASTM D5293	58
<b>Viscosity @ 40°C cSt</b>	ASTM D445	60.0
<b>Viscosity @ 100°C cSt</b>	ASTM D445	10.8
<b>Viscosity Index</b>	ASTM D2270	172
<b>Pour Point, °C</b>	ASTM D97	-45
<b>Flash Point, °C</b>	ASTM D92	201
<b>Sulfated Ash, wt. %</b>	ASTM D874	0.8
<b>HTHS Vis, cP @ 150°C</b>	ASTM D4741	3.3



# NORTH 69 ELITE EURO

Full Synthetic Motor Oil

## Health & Safety

When used as directed and in accordance with the Material Safety Data Sheet (MSDS), this product is not expected to pose health risks.

To request an MSDS, Please contact your direct sales Distributor or via email [info@north69oils.com](mailto:info@north69oils.com) or call 1-888-660-2913

This product is intended for its specified use only. When disposing of used oil, follow proper environmental protection guidelines.

## Products Numbers

Product Name	Package Size	Part Numbers
SAE 0W-30 EURO SP Full Synthetic	Bottle 1L	N69ET-S7059
	Box (1L X 12)	N69ET-S7059X12
	Jug 5L	N69ET-S7019
	Box (5L x 4)	N69ET-S7019X4
	Jug 18.9L	N69ET-S7089