



NORTH 69 ELITE EURO

Full Synthetic Motor Oil

Features & Benefits

- ★ Outstanding protection for cold starts
- ★ Superior defense against engine wear
- ★ Resists breakdown from heat and oxidation
- ★ Maintains stability under high temperatures
- ★ Helps prevent sludge and deposit buildup

Product Description

NORTH 69 Full Synthetic is engineered with ultra-refined synthetic base oils and advanced additive technology. It delivers instant protection from the moment you start your engine, even in extreme cold (-40°C). It not only meets but exceeds API SP standards and outperforms the stringent requirements set by both domestic and international automakers for high performance engines.

Properties

- Minimizes oil evaporation and burn-off at high temperatures
- Special detergent formula prevents sludge and deposit buildup, ensuring a clean engine
- Enhances engine longevity and reliability under extreme conditions
- Excellent resistance to aging for extended oil life

Specifications & Approvals

Meets or Exceeds	SAE 0W-40
API: CF	✓
API: SP, SN PLUS, SN	✓
ACEA: A3/B4	✓
Fiat: 9.55535-M2	✓
MB: 229.3, 229.5	✓
VW: 502 00, VW 503 01, VW 505 00	✓
Nissan Genuine Performances	✓
Porsche: A40	✓

Typical Results

SAE Grade	Test Method	SAE 0W-40
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8413
Viscosity @ 40°C cSt	ASTM D445	78.3
Viscosity @ 100°C cSt	ASTM D445	13.8
Pour Point, °C	ASTM D97	-42
Flash Point, °C	ASTM D92	230

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals. Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 22-37-82.



NORTH 69 ELITE EURO

Full Synthetic Motor Oil

Health & Safety

When used as directed and in accordance with the Material Safety Data Sheet (MSDS), this product is not expected to pose health risks.

To request an MSDS, Please contact your direct sales Distributor or via email info@north69oils.com or call 1-888-660-2913

This product is intended for its specified use only. When disposing of used oil, follow proper environmental protection guidelines.

Products Numbers

Product Name	Package Size	Part Numbers
SAE 0W-40 EURO Full Synthetic	Bottle 1L	N69ET-E8059
	Box (1L X 12)	N69ET-E8059X12
	Jug 5L	N69ET-E8019
	Box (5L x 4)	N69ET-S8019X4
	Jug 18.9L	N69ET-E8089