



Product Description

NORTH 69 Transmission Fluid Oil

provides ultimate transmission protection and peak performance in passenger cars, sports utility vehicles and light trucks. It also provides excellent hydraulic performance in industrial applications where low-temperature fluidity or leak detection is an important requirement.

NORTH 69 Transmission Fluid Oil

is Formulated with select base stocks for added resistance to thermal breakdown.

NORTH 69 Transmission Fluid Oil

Provides active anti-wear agents to protect critical transmission components.

Properties

- Excellent oxidation stability.
- Helps provide protection against rusting and corrosion.
- Contains an anti-foaming additive.

NORTH 69

Transmission Fluid Oil

Features & Benefits

- ★ Superior cold start up protection
- ★ Exceptional wear protection
- ★ Resists degradation due to heat and oxidation
- ★ High temperature volatility resistance
- ★ Reduces deposit and sludge formation

Specifications & Approvals

Meets or Exceeds	CVT	Meets or Exceeds	CVT
Mini Cooper (EZR 799/ EZL 799A/ ZF CVT V1)	✓	Audi/VW (TL 52180; G 052 180; G 052 516)	✓
Mitsubishi DiaQueen (CVTF-J1, CVTF-J4)	✓	BMW 8322 0 136 376/8322 0 429 154 (EZR799/799A)	✓
Mercedes Benz CVT28, 236.20	✓	Nissan (NS-1, NS-2, NS-3)	✓
Dodge / Jeep (NS-2 / CVTF+4 /Mopar CVT 4)	✓	Punch EZL 799/EZL 799A	✓
Ford CFT30/WSS-M2C933-A /Motorcraft XT-7-QCFT	✓	Toyota (CVTF TC, CVTF FE)	✓
GM/Saturn (DEX-CVT, CVTF I-Green2)	✓	Renault ELFMATIC	✓
Honda (HMMF, HCF-2)	✓	Subaru (NS-2 / Lineartronic CVTF, i-CVTF, K0425Y0710)	✓
Daihatsu Amix CVTF-DC, CVTF-DFE	✓	e-CVTF, High Torque	
Hyundai/Kia CVTF (SP-CVT-J1)	✓	Suzuki (TC / NS-2 / CVTF Green 1, Green 2, CVTF 3320)	✓
Mazda CVTF 3320	✓	Shell Green 1V	✓

Typical Results

SAE Grade	CVT
Viscosity (D445) cSt at 40 °C cSt at 100 °C	33.8 7.21
Viscosity Index (D2270)	185
Flash Point (D93) (°C) PMCC	200
Brookfield Viscosity cP -40°C	12,300
Pour Point (D97) (°C)	-51

Supporting data available to demonstrate acceptable performance. Check with your sales associate for latest product approvals.

Please note, these are typical performance indicators and can change without notice.

This data sheet replaces previous versions prior to 22-37-82.



NORTH 69

Transmission Fluid Oil

Health & Safety

This product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

To request an MSDS, Please contact your direct sales Distributor or via email info@north69oils.com or call 1-888-660-2913

This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Products Part Numbers

Product Name	Package Size	Part Numbers
CVT Full Synthetic	Bottle 0.946L	N69TS1136
	Box (0.946L X 12)	N69TS1136X12
	Bottle 1L	N69TS1135
	Box (1L x 12)	N69TS1135X12
	Jug 4.73L	N69TS1137
	Box (4.73L x 4)	N69TS1137X4
	Jug 5L	N69TS1131
	Box (5L x 4)	N69TS1131X4
	Jug 18.9L	N69TS1138
	Keg 60L	N69TS1132
	Drum 208L	N69TS1133
	Tote 1040	N69TS1134
	Bulk	N69TS11350