



Product Description

NORTH 69 Transmission Fluid Oil

provides ultimate transmission protection and peak performance in passenger cars, sports utility vehicles and light trucks. It also provides excellent hydraulic performance in industrial applications where low-temperature fluidity or leak detection is an important requirement.

NORTH 69 Transmission Fluid Oil

is Formulated with select base stocks for added resistance to thermal breakdown.

NORTH 69 Transmission Fluid Oil

Provides active anti-wear agents to protect critical transmission components.

Properties

- Excellent oxidation stability.
- Helps provide protection against rusting and corrosion.
- Contains an anti-foaming additive.

NORTH 69

Transmission Fluid Oil

Features & Benefits

- ★ Superior cold start up protection
- ★ Exceptional wear protection
- ★ Resists degradation due to heat and oxidation
- ★ High temperature volatility resistance
- ★ Reduces deposit and sludge formation

Specifications & Approvals

Meets or Exceeds	UNI ATF	Meets or Exceeds	UNI ATF
Aisin JWS 3309, 3324 (all OEM's)	✓	Hino Blue Ribbon ATF	✓
Allison C-3, C-4	✓	Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	✓
Audi 5HP LT71141, G 052 162-A1/A2, G 052 025 A2, 053 025 A2, 060 162, 055 540 A2, 052 990, 052 055	✓	Hyundai/Kia SP-IV, SP-IV M, SPH-IV, SP-IV RR, DexII/SP-II, JWS 3314, 9683, 04000090SG, NUMM040 CH20 Red-1	✓
Bentley PY112995PA	✓	IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	✓
BMW JWS 3309, LA2634, 7045E, LT71141, ETL 8072B, ZF 5HP18FL, 19FL, 5HP24, 5HP30	✓	ISUZU BESCO ATF-II, III, Isuzu SCS, ATF-III, ATF SP, 08200-9001	✓
Bosch TE-ML 09	✓	Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238, K17, 20292, 8432, 02JDE26444, WSS-M2C922A1	✓
CAT TO-2	✓	JASO 1A-LV	✓
Chrysler 05127382AA(MB 236.12), 68043742AA(D-VI), 68157995AA(ZF 8 & 9), 68157995AB, 68171866AA(SP-IV), Mopar 8 & 9 fluid 68218925AA (ZF 8HP45 & ZF 9HP45)	✓	Land Rover LR023288	✓
Chrysler AS68RC, AS69RC (T-IV), Diamond SP-III, ATF+3, ATF+4	✓	Lexus JWS 3309	✓
Daewoo LT 71141	✓	MAN 339A, 339 Type V2, V1, Z2, Z1	✓
Daihatsu AMMIX ATF D-II, D-III SP	✓	Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317, T-IV	✓
Esso LT 71141	✓	MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.14, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9	✓
Fiat T-VI, JWS 3309	✓	Mini Cooper T-IV, MINI P/N 83 22 0 402 413	✓
Ford M2C166H (XL-12), 138CJ, 922A1, 924A, JWS 3309, XT-2-QDX (Mercon V), XT-2-QSM (Synthetic Mercon), Ford FNR5, (Mazda M5, XT-9-QMM5), XT8QAW	✓	Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATFMA1, PA	✓
Ford Mercon LV (FF-WSS M2C938A/SF, XT-10-QLV)	✓	NAG-1 (Chrysler, Jeep, Cherokee)	✓
Fuchs 3353	✓	Nissan Matic C, D, J, K, P, S, 402	✓
FUSO ATF-II, SPIII, A4	✓	Porsche P/N 999 917 547 00 (A2), ZF 5HP16FL, 19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 000 043 205 28	✓
GM Dexron HP, Dexron VI, Dexron III (H,G,F,E,D) Dexron II (D,E) Dexron, AW1	✓	SAAB T-IV, 3309, 93 165 147, 93 160 393	✓
GM Autotrak II (Transfer Case Fluid)	✓	Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466, 88900925, 93160393	✓
GM (GMC, Opel, Saturn) 88863400/88863401(WSS ATF), JWS 3309, 19 40 700, 19 40 767, 21005966 Transaxle, 22 17466, 88900925(T-IV), 9986195 (Aisin AW), AS69RC	✓	Shell L 12108, 3403 M115, LA2634, ETL-8072B, M-1375.4	✓
GMN 10060	✓	Subaru ATF 5AT, Dex II, AT OIL 5D06, ATF, ATF HP	✓
Vickers M-2950-S, I-286-S	✓	Suzuki ATF 2326, 2384K, JWS 3309, 3314, 3317, AT OIL 5D06	✓
Voith 55.6335 (G607), Svc Bln #013 and #118	✓	Texaco 7045-E, 8072B, N402	✓
Volvo 97325, 97335, CE 97340, CE97341/AT-101, CE 97342/ AT-102, 1161521, 1161621, 1161540, 1161640, 31256774, 31256675	✓	Toyota D-II, D-III, Hybrid, T-II, T-III, T-IV, WS	✓
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342/P/N 1161540-8	✓	VW 5 HP ZF5 HP 30, 18FL, 19FL, 24A, G-055-025 A2, G-055-540, G-055-162 (ZF Lifeguardfluid 5), G-055-162-A2, A6 (ZF Lifeguardfluid 6 Plus), G-060-162 (ZF Lifeguardfluid 8), G US 000 162, TL 52540 A, VW G 052 162 A1, A2 A6, 099, VW TL52162 (LT71141)	✓
		ZF: all 3 & 4 speed, 8 speed, 9 speed, ZF TE-ML 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 14C, 16L, 17C, 21L	✓



NORTH 69

Transmission Fluid Oil

Health & Safety

This product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

To request an MSDS, Please contact your direct sales Distributor or via email info@north69oils.com or call 1-888-660-2913

This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Typical Results

SAE Grade	UNI ATF
Viscosity (D445) cSt at 40 °C cSt at 100 °C	28.6 5.80
Viscosity Index (D2270)	152
Flash Point (D93) (°C) PMCC	220
Brookfield Viscosity cP -40°C	10,300
Pour Point (D97) (°C)	-51

Products Part Numbers

Product Name	Package Size	Part Numbers
Universal ATF Full Synthetic	Bottle 0.946L	N69TS1126
	Box (0.946L X 12)	N69TS1126X12
	Bottle 1L	N69TS1125
	Box (1L x 12)	N69TS1125X12
	Jug 4.73L	N69TS1127
	Box (4.73L x 4)	N69TS1127X4
	Jug 5L	N69TS1121
	Box (5L x 4)	N69TS1121X4
	Jug 18.9L	N69TS1128
	Keg 60L	N69TS1122
	Drum 208L	N69TS1123
	Tote 1040	N69TS1124
	Bulk	N69TS11250